



# Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022  
Issue date: 2026-03-10 Revision date: 2026-03-10 Version: 1.0

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Product name : Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricant

#### 1.4. Supplier's details

##### Manufacturer

International Lubricants, Inc  
309 South Cloverdale Street, D26  
Seattle, WA, 98108  
USA  
T 206-762-5343  
[contact@lubegard.com](mailto:contact@lubegard.com)

##### Distributor

Add the name, address and tel. number of the Canadian manufacturer or importer who operates in Canada.

#### 1.5. Emergency phone number

Emergency number : VelocityEHS (formally Chemtel) (813) 248-0573  
Velocity EHS (24 hours) 1-800-255-3924 (North America)

### SECTION 2 Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Skin sensitization, Category 1

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) : Warning  
Hazard statements (GHS) : May cause an allergic skin reaction  
Precautionary statements (GHS) : If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
Avoid breathing dust, fume, gas, mist, vapours, spray.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves, protective clothing, eye and face protection.  
If on skin: Wash with plenty of water.  
Take off contaminated clothing and wash it before reuse.

# Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

If skin irritation or rash occurs: Get medical advice or attention.  
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

Not applicable

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Distillates, petroleum, hydrotreated heavy paraffinic	Distillates, petroleum, hydrotreated heavy paraffinic Petroleum distillates, hydrotreated heavy paraffinic / Distillates (petroleum), hydrotreated heavy paraffinic / Paraffin oil / Distillates, petroleum, hydrotreated heavy paraffinic (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20-50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.) / Heavy paraffinic hydrotreated distillate / HYDROGENATED MINERAL OIL / Hydrogenated mineral oil	CAS-No.: 64742-54-7	30 – 60
1,3,4-Thiadiazole, 2,5-bis(octylidithio)-	1,3,4-Thiadiazole, 2,5-bis(octylidithio)- 2,5-Bis(octylidithio)-1,3,4-thiadiazole / Thiadiazole (1,3,4), 2,5-bis(octylidithio) / 2,5-bis(Octylidithio)-1,3,4-thiadiazole	CAS-No.: 13539-13-4	0.1 < 1

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

# Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 4 First-aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Powder, water spray, foam, carbon dioxide.
Unsuitable extinguishing media	: Do not use water jet.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon. Oxides of phosphorus.
-------------	---

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

#### For non-emergency personnel

No additional information available

#### For emergency responders

Environmental precautions	: Prevent entry to sewers and public waters.
---------------------------	--

# Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 6.2. Methods and materials for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Use only in well-ventilated areas. Handle and open container with care. When using do not eat, drink or smoke.
- Hygiene measures : Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

### 7.2. Conditions for safe storage, including incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
- Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

#### Eye protection:

Safety glasses or goggles are recommended when using product.

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

# Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### Other information:

Handle according to established industrial hygiene and safety practices. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear. Transparent.
Colour	: Red
Odour	: Sweet / Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 109 °C (228 °F) ASTM D93
Relative evaporation rate (butylacetate=1)	: Negligible.
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: < 0.1 mm Hg
Relative vapour density at 20°C/ 68 °F	: No data available
Relative density	: No data available
Density	: 0.87 g/cm <sup>3</sup> @ 24°C (75.2 °F)
Solubility	: Insoluble.
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 30 mm <sup>2</sup> /s @ 40 °C (104 °F); 6.25 cSt @ 100 °C (212 °F)
Explosive limits	: No data available
Particle characteristics	: No data available

### Distillates, petroleum, hydrotreated heavy paraffinic

Boiling point	207 – 750 °C Atm. press.: 101,325 kPa
Flash point	98 – 344 °C Atm. press.: 101,325 kPa
Vapour pressure	< 0.1 hPa Temp.: 20 °C

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

# Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 10.4. Conditions to avoid

Heat. Incompatible materials.

### 10.5. Incompatible materials

Oxidizers.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Oxides of phosphorus.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.  
Acute toxicity (dermal) : Not classified.  
Acute toxicity (inhalation) : Not classified.

#### Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HP)

Skin corrosion/irritation : Not classified.  
Serious eye damage/irritation : Not classified.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified.  
Carcinogenicity : Not classified.  
Reproductive toxicity : Not classified.  
STOT-single exposure : Not classified.  
STOT-repeated exposure : Not classified.

#### Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified.

#### Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

Viscosity, kinematic	1.99 – 847 mm <sup>2</sup> /s Temp.: '40°C' Parameter: 'mm <sup>2</sup> /s' 'mm <sup>2</sup> /s'
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

# Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 12 Ecological information

#### 12.1. Ecotoxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified.  
Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

#### 12.2. Persistence and degradability

Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement	
Persistence and degradability	Not established.

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Rapidly degradable

1,3,4-Thiadiazole, 2,5-bis(octyldithio)- (13539-13-4)	
Persistence and degradability	Rapidly degradable

#### 12.3. Bioaccumulative potential

Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement	
Bioaccumulative potential	Not established.

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Ozone : Not classified.  
Fluorinated greenhouse gases : No  
Other information : No other effects known.

### SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### SECTION 14 Transport information

In accordance with DOT / TDG

#### 14.1. UN Number

UN-No. (DOT) : Not regulated  
UN-No. (TDG) : Not regulated

# Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not regulated

Proper Shipping Name (TDG) : Not regulated

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : Not regulated

#### TDG

Transport hazard class(es) (TDG) : Not regulated

### 14.4. Packing group

Packing group (DOT) : Not regulated

Packing group (TDG) : Not regulated

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

#### DOT

Not regulated

#### TDG

Not regulated

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### 15.2. International regulations

No additional information available

### 15.3. State regulations



#### WARNING:

This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date : 2026-03-10

Issue date : 2026-03-10

# Lubegard® Highly Friction Modified Automatic Transmission Fluid Supplement

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

---

Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2026

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.